

HIGH PERFORMANCE SCREEN FABRIC  
FOR DOMESTIC & CONTRACT MARKET



# RAY-SCREEN®

**320  
PURE  
3%**

Composition	65% PVC - 35 % Polyester
Weight	± 320 g/m <sup>2</sup>
Thickness	± 0,45 mm
Width	300 cm
Fire Classification	M1 - B1
Health & Safety	Greenguard - Oeko-Tex®
Tensile strength (warp)	150 daN/5cm
Tearing strength (warp)	>5 daN
Tensile strength (weft)	120 daN/5cm
Tearing strength (weft)	>7 daN
Colour Fastness	7 (ISO 105 B02)
Microorganisms	ISO 846



Colour	T <sub>s</sub>	R <sub>s</sub>	A <sub>s</sub>	T <sub>UV</sub>	T <sub>v</sub>	OF
col01	22	67	11	3	20	3
col04	10	35	55	2	8	3
col15	17	51	32	5	12	3

Interior		
g <sub>tot</sub>	Fc	Class
0,35	0,59	2
0,43	0,73	1
0,39	0,66	1

Ts Solar Transmittance - Rs Solar Reflectance - As Solar Absorptance - Tuv UV Transmittance - Tv Visible Light Transmittance  
OF Openness Factor

Measurements according to EN410, Glass Type C  
Classification according to EN14501

